


# MATERIAL SAFETY DATA SHEET



CATHEDRAL STONE® PRODUCTS

*In the Lab. In the Field. Innovation.*



## NFPA 704 DESIGNATION HAZARD RATING

4 = Extreme      3 = High      2 = Moderate  
1 = Slight      0 = Insignificant

WHMIS CLASSIFICATION: B3, D2B

**PATENT PROTECTED TECHNOLOGY**

Issue Date: 2/21/2008	Supersedes: 4/24/2007
-----------------------	-----------------------

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT IDENTIFIER:** S-307

**PRODUCT USE:** Graffiti and Overspray Remover

**Cathedral Stone Products, Inc.**  
7266 Park Circle Drive  
Hanover, MD 21076

Telephone: (800) 684-0901  
Facsimile: (410) 782-9150  
www.cathedralstone.com

In case of transportation emergency or product spill, contact:  
CHEMTREC @ 800-424-9300 (24 hrs)  
Customer Code: CDTS

## 2. COMPOSITION & INFORMATION ON INGREDIENTS

<u>Component</u>	<u>% weight</u>	<u>CAS #</u>	<u>SARA Title III Section 313</u>	<u>RCRA</u>	<u>CARCINOGENICITY (As per 29CFR 1910-1200)</u>
Butyl carbitol	< 40	112-34-5	Not Listed	No	No
Aromatic Alcohol	< 15	100-51-6	Not Listed	No	No
Dimethyl Sulfoxide	< 15	67-68-5	No	No	No
Dipropylene glycol methyl ether	< 15	34590-94-8	No	No	No

All components are listed in the TSCA inventory (U.S.) and on the DSL (Canada).  
The above information is based on component manufacturer's Material Safety Data Sheets.

## 3. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Liquid	<b>Vapor Pressure</b>	Not determined
<b>Odor</b>	Mild	<b>Vapor Density</b>	Not determined
<b>Odor Threshold</b>	N/A	<b>Evaporation Rate (n-Butyl Acetate=1)</b>	< 1
<b>Molecular Formula</b>	Mixture	<b>VOC content</b>	286.8 g/l (2.39 lbs/gal)
<b>Molecular Weight</b>	N/A	<b>% Volatiles</b>	Not determined
<b>Boiling Point</b>	Not determined	<b>Solubility in Water</b>	Less than 10%
<b>Freezing Point</b>	Not determined	<b>pH (direct reading)</b>	Not applicable
<b>Specific Gravity</b>	0.994	<b>Density (lbs/gal)</b>	8.29

## 4. STABILITY & REACTIVITY

<b>GENERAL:</b>	This product is stable and hazardous polymerization will not occur.
<b>CONDITIONS TO AVOID:</b>	Hot or cold storage.
<b>INCOMPATIBLE MATERIAL:</b>	Strong oxidizers, acids and alkalis.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Thermal decomposition (combustion) will produce carbon monoxide and dioxide.
<b>SENSITIVITY TO MECHANICAL IMPACT:</b>	This product is not sensitive to mechanical impact.
<b>SENSITIVITY TO STATIC DISCHARGE:</b>	This product is not sensitive to static discharge.



## 9. HANDLING AND STORAGE

**STORAGE TEMPERATURE:** 4 - 30 °C (39 - 86° F)

**STORAGE PRESSURE:** Ambient

**GENERAL:** Prior to each use, mix well. Store in a well-ventilated area away from heat, open flames or any ignition sources. Avoid contamination of any kind. Potential immersion elements such as drum pumps and hoses should be removed after each use. Empty containers should be thoroughly rinsed with water and disposed of according to local regulations. Do not completely fill containers with the resulted paint waste. Until mostly dry, wet paint waste can have the tendency to slightly expand, therefore do not seal containers airtight to allow a breathing period.

**Cautionary Note** Care should be exercised when moving in or around product application areas (particularly oversprayed areas) as contacted surfaces become very slippery.

## 10. ACCIDENTAL RELEASE MEASURES

**LAND SPILL:** Wearing recommended protective clothing, dike spill using soil, sand or compatible commercial absorbent. Pick up bulk of product using pumps or vacuum truck or absorb product in sand or commercial absorbent. Place in approved containers for recovery or disposal. Flush spill area with water, collect rinsates and containerize for disposal. Prevent runoff from contaminating storm sewers, streams or other bodies of fresh water. Rinsates may be disposed of in sewers leading to a municipal or city treatment facility or an internal treatment facility.

**WATER SPILL:** This material is considerably soluble in water. Stop or divert water flow. Dike contaminated water and remove from disposal and/or treatment. Notify all downstream users of possible contamination.

## 11. DISPOSAL CONSIDERATIONS

**RCRA 40 CFR 261 CLASSIFICATION:** Not Classified

**U.S. EPA WASTE NUMBER/DESCRIPTION:** None

If this product is disposed of as shipped, it does not meet the criteria of a hazardous waste under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste of Subpart C, nor is it listed as a hazardous waste under Subpart D. As a non-hazardous liquid waste, it should be disposed of in accordance with all local, state or provincial, and federal regulations. Consult state or provincial or local officials for proper disposal method.

## 12. TRANSPORTATION INFORMATION

**S-307 is NOT regulated as a hazardous material under the regulations of the U.S. DOT, IMDG or in Canada TDG.**

This Material Safety Data Sheet is provided as an information resource only. It should not be taken as a warranty or representation for which Cathedral Stone Products, Inc. assumes legal responsibility. While Cathedral Stone Products, Inc. believes the information contained herein is accurate and compiled from sources believed to be reliable, it is the responsibility of the user to investigate and verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with applicable federal, state, provincial and local regulations.